

FURUNO**MES**
Mobile Earth Station

Model: FELCOM20

FEATURES OF FELCOM20

- ▶ Inmarsat-C Ship Earth Station terminal for GMDSS application
- ▶ Enables versatile communication such as E-mail, Telex, Fax, EGC (Enhanced Group Call), and data reporting/polling
- ▶ Operable via touch panel and keyboard
- ▶ Intuitive icon-based interface for easy operation
- ▶ Compatible with the following optional units:
 - Distress Alert / Received Call Unit IC-305
 - Alarm Unit IC-306
 - SSAS Alert Unit IC-307
 - Junction Box IC-318
 - Printer PP-520
- ▶ Optional printer (PP-520) required to meet EGC receiver performance standards
- ▶ Compliant with the latest IMO performance requirements and IEC testing standards
- ▶ Compliant with GMDSS, LRIT, and SSAS*

*The optional SSAS Alert Unit (IC-307) is required to meet the performance requirements of the SSAS function.

GMDSS
Global Maritime Distress and Safety System**LRIT**
Long-Range Identification and Tracking of ships**SSAS**
Ship Security Alert System



The Inmarsat logo consists of a stylized green and blue wave-like graphic above the word "inmarsat" in a bold, lowercase, sans-serif font. Below it is the website address "www.furuno.com".

SPECIFICATIONS


Product Name	Inmarsat-C Mobile Earth Station
Transmitting Frequency	1626.5 - 1646.5 MHz
Receiving Frequency	1537.0 - 1544.2 MHz
Channel Interval	5 kHz
Transmit Modulation Rate and Method	600, 1200 sps Unfiltered BPSK
Receive Modulation Rate and Method	1200 sps Unfiltered BPSK
Receiving Performance Index (G/T)	-23 dB/K or higher (at elv. 5°)
Transmit EIRP	12 - 16 dBW (at elv. 5°)
Power Supply	12-24 VDC

ENVIRONMENT


Temperature Antenna Unit	-35 °C to + 55 °C
Temperature Shipboard Equipment	-15 °C to + 55 °C
Relative Humidity	95% at 40°C

Antenna Unit**IC-120**
1.5 kg 3.31 lb**Terminal Unit****IC-220**
Tabletop Mount 4.1 kg 9.04 lb**Distress Alert / Received Call Unit****IC-305**


0.34 kg 0.75 lb

**Alarm Unit****IC-306**


0.33 kg 0.73 lb

**SSAS Alert Unit****IC-307**

0.35 kg 0.77 lb


**Junction Box****IC-318**

0.75 kg 1.65 lb


**EQUIPMENT LIST**

	Item Name	Model No.	Quantity
Standard	Antenna Unit	IC-120	1
	Terminal Unit	IC-220	1
	Junction Box	IC-318	1
	SSAS Alert Unit	IC-307*	2
	Keyboard		1
	Installation Materials		1 set
Option	GNSS Antenna Unit	GPA-022S	-
	Distress Alert / Received Call Unit	IC-305	-
	Alarm Unit	IC-306	-
	SSAS Alert Unit	IC-307	-
	Printer	PP-520	-
	AC/DC Power Supply Unit	PR-241	-

* Included in standard configuration only for SSAS specification.

INTERCONNECTION DIAGRAM**Printer****PP-520**

4.8 kg 10.58 lb



Beware of similar products

The brand, product names, trademarks, registered trademarks, or service marks mentioned in this document belong to their respective holders.

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE