Hi-Brite Multi Touch Monitor Specifications

| | 17" Hi-Brite Multi Touch Monitor | 19" Hi-Brite Multi Touch Monitor | 24" Hi-Brite Multi Touch Monitor |
|-----------------------------|---|--|------------------------------------|
| | MU175T | MU195T | MU245T |
| | | | |
| DISPLAY CHARACTERISTICS | | | |
| Screen Size | 17 inches, 5:4 Aspect Ratio* | 19 inches, 5:4 Aspect Ratio* | 24 inches, 16:9 Wide Aspect Ratio* |
| Resolution | 1280 x 1024 | 1280 x 1024 | 1920 x 1080 |
| Contrast Ratio (typical) | 1,000 : 1 | 1,000 : 1 | 3,000 : 1 |
| Viewing Angle (typical) | +/- 80° (typical) (Up/Down/Left/Right) | +/- 89° (typical) (Up/Down/Left/Right) | |
| Max Brightness (typical) | 1,000 NITS Hi- Brite | 1,000 NITS Hi- Brite | 1,000 NITS Hi- Brite |
| INTERFACE | | | |
| Device Port 1.2 | 1 port | | |
| DVI (DVI-D) | 2 ports | | |
| Composite Video (NTSC/PAL) | 2 ports (BNC) | | |
| VGA Out | 1 15-Pin D-SUB | | |
| Supported Resolutions | VGA to SXGA | VGA to SXGA | VGA to WUXGA |
| POWER SUPPLY | | | |
| | 115 & 230 VAC, 50/60Hz + 24 VDC Note: You may connect either AC or DC power or both. When both sources are connected, power will be sourced from the AC input. If AC input is lost, there will be an uninterrupted switch-over to DC input. | | |
| ENVIRONMENT (EN60529 test m | nethod) | | |
| Temperature | -15°C to +55°C | | |
| Waterproofing | IP66 (front panel), IP22 (rear panel) | | |

*Note: Only the MU245T should be used as a remote display for the TZT14 or TZT9, as this monitor has a wide aspect ratio for proper video scaling of the TZT MFD video output.

Dimensions and Weights







MU175T/195T/245T Hi-Brite Multi Touch Marine Monitors

Refer to the manual for complete flush mounting dimensions and instructions.











style

C C

a B

0

GLASS BRIDGE DISTINCTION

The Furuno Multi Touch Monitor series offers an edge-to-edge glass design, giving your bridge or helm a stylish, rich and beautiful appearance. They feature Glass Display Controls and brilliant LED Backlighting, making them easy to see and operate at virtually any angle. These monitors are the perfect match for our NavNet TZtouch/TZtouch2 Black Box systems, giving you a high-tech, all glass bridge.



SUNLIGHT & NIGHT TIME VIEWABILITY

0

31.1 ft 31.5 ft

The marine environment provides one of the most challenging settings for electronics. Furuno's monitors not only meet the challenge, but exceed it! Whether it is a flybridge or an enclosed pilot house, these monitors perform flawlessly. Unlike most off-the-shelf multi touch monitors that have a max brightness of 250 cd/m², our MU175T/195T/245T multi touch monitors have a brilliance of 1,000 cd/m2. That's 300% brighter than typical off-the-self monitors! Our monitors can also be fully dimmed, so your night vision is not affected by the gray glow that is commonly experienced with most off-the-shelf monitors.

MU175T/195T/245T

Experience the brilliance of a Furuno Multi Touch Glass Bridge

MU245T 24-inch, 1920 x 1080, 16:9 Aspect Ratio



bonding

MADE TO WITHSTAND THE ELEMENTS

While monitors for many industrial and entertainment applications have to withstand heavy usage, marine displays face some of the toughest challenges. Condensation, salt water exposure, sunlight reflection, night vision, and overheating, are just some of the factors that marine displays face. These monitors are optically bonded, giving them much better sunlight viewability (reflection by the sun is reduced by up to 94%), as well as preventing condensation from forming.

PIP & PBP



With multiple video inputs (1 Device Port 1.2, 2 DVI, 2 NTSC/PAL (BNC), and 1 VGA Out 15-Pin D-SUB), Furuno's Multi Touch Monitor series gives you the ability to display Picture In Picture (PIP) and Picture By Picture (PBP). This allows you to clearly display your navigation situation on the main screen, while also keeping track of the news or your favorite sports team, when connected to an on-board TV/DVD player.



ML1195T 19-inch 1280 x 1024 5:4 Aspect Ratio

multi power

NO MORE POWER STRUGGLES

Powering your monitors should not be a struggle, which is why these monitors allow you to connect either AC or DC power. You can even connect both sources! When both power sources are connected, power will be sourced from the AC input. If the AC input is lost, there will be an uninterrupted switchover to the DC input.