COLOR DGPS/PLOTTER GP-1850D COLOR GPS/PLOTTER GP-1850 Operator's Guide

The purpose of this operator's guide is to provide the basic operating procedures for this equipment. For detailed information, refer to the operator's manual.

Turning the Power On/Off

Press and hold down the [POWER/BRILL] switch.

Adjusting Tone and Brilliance

- 1. Press the [POWER/BRILL] key with a touchand-release action.
- 2. Press the appropriate soft key or cursor pad to adjust.

Displaying Electronic Chart at Power Up

Insert mini chart card in slot and turn on the power.

Selecting Nav Data Displays

Press the soft key NAV L/L (WPT, S/C).

Changing Chart Scale

Press the soft key [ZOOM IN] to enlarge; [ZOOM OUT] to shrink.

Turning the Cursor On/Off

Cursor On: Operate the cursor pad. Cursor Off: Press the soft key [CENTER].

Shifting the Cursor

Operate the cursor pad.

Shifting the Display

Press and hold down the cursor pad.

Returning Own Ship to Screen Center

Press the soft key CENTER.

Changing the Plot Interval

- 1. Press the [MENU] key to show the main menu.
- 2. Press the soft key CHART SETUP OPTIONS to show the chart setup options menu.
- 3. Press the soft key TRACK CON-TROL.
- Press ▲ or ▼ to select TIME INTERVAL or DIST INTERVAL.
- 5. Press the soft key EDIT.
- 6. Key in the interval desired.



Entering Mark

- 1. Press the [MENU] key and the soft key DIS-PLAY OPTIONS.
- 2. Press ▼ to select OPERATION MODE.
- 3. Press the soft key EDIT.
- 4. Press \blacksquare to select FISHING.
- 5. Press the soft key ENTER or the [ENTER] key.
- 6. Press the PLOT key to display the plotter display.
- 7. Press the [HIDE/SHOW] key to display the soft key MARK ENTRY.
- 8. Press the soft key MARK ENTRY.

When the cursor is displayed, a mark which its shape and color are presetted is entered to cursor position. When the cursor is not displayed, a mark is entered to own ship position. The mark attributes can be changed by the soft key MARK EDIT.

Stopping, Restarting Recording of Track

- 1. Press the [MENU] key.
- 2. Press the soft key CHART SETUP OP-TIONS.
- 3. Press the soft key TRACK CONTROL.
- 4. Press the soft key STOP TRACK. NOT TRACKING indication appears at the bottom of the display.

To restart recording, press the soft key START TRACK.

Entering Waypoints at Own Ship Position

Press the [SAVE/MOB] key with a touch-and-release action.

Entering Waypoints By Cursor

- 1. Press the [WPT/RTE] key.
- 2. Press the soft key WAYPOINTS.
- 3. Press the soft key WAYPOINT BY CURSOR to show the plotter display.

- 4. Operate the cursor to place the cursor on the position you want to enter the waypoint.
- 5. Press the soft key NEW WPT.
- 6. Press the soft key SAVE.

Registering Routes

- 1. Press the [WPT/RTE] key.
- 2. Press the soft key ROUTES.
- 3. Press the soft key NEW ROUTE.
- 4. Press the soft key LOCAL LIST or ALPHA LIST.
- 5. Press \blacktriangle or \blacktriangledown to select a waypoint.
- 6. Press the soft key ADD WPT.
- 7. Repeat step 5-7.
- 8. Press the soft key SAVE.

Setting Destination by Waypoint Number

- 1. Place the cursor on the waypoint you want to go on the plotter display.
- 2. Press the soft key GO TO WPT.

Cancelling Destination

- 1. Press the [WPT/RTE] key.
- 2. Press the soft key LOG.
- 3. Press \blacktriangle or \triangledown to select the waypoint desired.
- 4. Press the soft key STOP.
- 5. Press the [ENTER] key to select YES on the confirmation window.
- 6. Press the soft key RELEASE to show the confirmation window.
- 7. Press the [ENTER] key to select YES.

Setting Arrival Alarm

- 1. Press the [ALARM] key to show the alarm menu.
- 2. Select ARRIVAL ALARM.
- 3. Press the soft key EDIT.
- 4. Press \blacktriangle or \blacktriangledown to select ON.
- 5. Key in the alarm range.
- Press the soft key ENTER.
 Silencing audible alarm: [CLEAR] key.
 Disabling alarm: Select OFF at step 3 above.



PUB.NO.OSE-43952-D (0005,TATA) GP-1850/1850D