

FURUNO

TZT3 Factory Reset/Clear

Save all valuable user data prior to conducting a reset, such as; waypoints, routes, tracks and user settings. Instructions for saving user data can be found in chapter 8 of the Operator's Manual, chapter 6 of the onboard eGuide.

From SERVICE Menu selection

- 1. Turn on the TZT12F/16F/19F and allow it to fully boot up normally.
- 2. Select "HOME" "SETTINGS" and "INITIAL SETUP"



3. Select "Service" and enter Password "FURUNO SERVICE". Don't forget the space and use all CAPS.



4. When Service menu boots up, you will need to hit CANCEL to bypass the factory touch pad and enter the service mode.

Inf	ormation	WWW	Marst	
This Mo	s is Enterin de.	ig of Facto	ry Mode. C	ancel is Serviceman
	1	2	3	-
	4	5	6	backspace
	7	8	9	E
		0		nten Int
		Cancel	No.	ок

5. Once into the service menu, select "UTILITY"

1950153-01.18 SELF TEST	SCREEN TEST	SENSOR TEST	UTILITY	EXIT SERVICEMAN	POWER OFF
est Items	Output Data	Auto Check Result	0	START	
				Elapsed time:00:00:00 Test count:00000000	
				Save Log (No Lo	gs)
				Event SW	OFF
				Internal Buzzer	OFF
				Intervals Co	ntinuous

6. Select "Factory Default"

8.

DATA/FILE WLAN MONITOR CAN BUS MONITOR refault Enter 1 2 3 refault Enter 1 2 3 refault Col Time TA Time 4 5 6 Mode Get 7 6 backs moving state Female 7 6 9	1950153-01.18 SELF TEST	SCREEN TEST	SENSOR	R TEST	UT	ILITY	EXIT SEP	VICEMAN	POWER OFF
Image Files Image Files </th <th>DATA</th> <th>/FILE</th> <th></th> <th>WLAN M</th> <th>DNITOR</th> <th></th> <th></th> <th>CAN BUS MONITOR</th> <th></th>	DATA	/FILE		WLAN M	DNITOR			CAN BUS MONITOR	
Image: Sector of the sector of th	Factory default	Setup							
V/TX Time ON Time TX Time 4 5 6 back pace Mode General 7 8 9 moving Indush Permore 6 0 6	Export Log Files	Setup							
Mode correlation for the second secon	Radar ON/TX Time Reset								
moving udak Petruch Permon 4 8 9	Intercept Mode	077							
• • •	Safety removing								

7. When the reset menu appears, touch the pull-down arrow and select "Factory Default (Delete All Settings) **WARNING**: You are about to clear the unit. Ensure you have backed up any desired user data!!

Note: Ensure that already been bac	t waypoints, routes & user settings have ked up. This procedure will wipe all info.
	Application Settings
	Marks and Routes
	Tracks
	Odometer
	Charts Unlock Codes
	Memory Cache
	Factory Default (Delete All Settings)
	Complete System Wipe
Hit the "RESET" selection	

Reset Menu
Factory Default (Delete All Settings) 🔸
Reset

9. The system will ask you "Are you Sure"? You should select "OK".

Reset Menu	Reset
Factor Angel States (Data in States) S) - OK CANCEL	Facto
Reset Exit	Reset

10. When the system says "delete succeeded"; select the "OK" button.

Reset M Facto	Aenu ctory Defeuit (Delete All Setti date succeded OK	nge) s) -	
Reset		Exit	

11. Select "EXIT"

Reset Menu		
Factory Defaul	lt (Delete All Setting	s) •
Reset		Exit

12. Select "POWER OFF" from the Service Man menu.

1950153-01.18 SELF TEST	SCREEN TEST	SENSOR TEST	UTI	LITY	EXIT SEF	RVICEMAN	POWER OFF
DAT	A/FILE	WLAN N	IONITOR			CAN BUS MONITOR	
Factory default							
Export Log Files	Read of the local division of the local divi		1				
Radar ON/TX Time Reset							
Intercept Mode	-						
Safety removing							
			-				

13. The unit is now ready to use and restore any settings or waypoint you wish to restore.